

线性硅光电池参数

外形 size mm*mm	光学参数		电参数						
	nm	p nm	Voc	Isc	ID	Rsh	Cj	tr	E=1000LX RL=100
			mV	μA	A		PF	μs	
					A光源E=100LX 最小值	E=0 VR=-1V 最大值	E=0 VR=-1V 最小值	E=0 VR=0	
		360-1100	800	360	1.5	10*10	10	200	0.5
	1.3*1.3	400-730	550	300	0.13	10*10	10	200	0.5
	1*2	400-1100	900	360	2	5*10	2*10	6	10*10
	2.4*2.8	320-1100	800	360	4	10*10	10	700	1
	2.4*2.8	400-730	550	300	0.45	10*10	10	700	1
	2.7*2.7	400-1100	900	360	6	10*10	10	25	50*10
	3.7*3.7	360-1100	800	360	8	5*10	2*10	4000	10
	3*5	360-1100	800	360	8	5*10	2*10	4000	10
	5.7*5.7	320-1100	800	330	18	5*10	2*10	4300	11
	5.7*5.7	250-1100	760	300	16	5*10	2*10	4300	11
	5.7*5.7	400-900	900	300	20	5*10	2*10	200	0.5
	7*7	360-1100	800	330	30	10	10	10000	25
	7*10	320-1100	760	330	40	10	10	10000	25
	9.9*9.9	320-1100	800	330	55	10	10	13000	30
	9.9*9.9	250-1100	760	300	50	10	10	13000	30

 原文地址：<http://www.china-nengyuan.com/tech/12843.html>